

- ◆ Input: 100~240VAC, 50/60Hz
- ◆ Output: 17W
- ◆ USB 5V
- ◆ DC 9V/12V Selectable
- ◆ POE 15V/24V Selectable
- ◆ 10400mAh Lithium battery long back up time
- ◆ Suitable for small DC Communication equipment, network peripherals



Specification

| Model | | MDU-POE 10 | | |
|--------------------------|---------------|---------------------|---------------------|--|
| Input voltage | | 100-240Vac/50-60Hz | | |
| Output Power | | 17W | | |
| Output | USB interface | POE interface | DC interface | |
| Output voltage(Optional) | 5Vdc | 15Vdc/24Vdc | 9Vdc/12Vdc | |
| Output polarity | / | +4,5pins -7,8pins | - - ● + | |
| Output voltage & current | 5V/2.5A | 15V/1.1A & 24V/0.7A | 12V/1.4A or 9V/1.8A | |
| QTY.&capacity of battery | | 2600mAhx4 | | |
| Unit dimension(mm) | | 176x110x35mm | | |
| Net weight(kg) | | 0.4kg | | |
| Operating temperature | | 0°C~40°C | | |
| Storage temperature | | -15°C~45°C | | |

* Product specifications are subject to change without notice.