

## MAR-63 Residual Current Circuit Breaker

### Application

MAR-63 RCCBs incorporate the same housing and installation features as the MCBs. With a range that includes pulse current sensitive and super immune devices, there's a unit for every application.



MAR-63 1P+N



MAR-63 3P+N

### Specification

Number of Poles	1P+N, 3P+N
Rated Current	16A, 25A, 40A, 63A
Rated Operational Voltage	230V/400V~, 240V/415V~
Earth-leakage Sensitivity	30mA, 100mA, 300mA
Trip Unit Technology	Electro-magnetic
Network Type	AC  /A
Standards	IEC/EN 61008-1
Rated Breaking Capacity (Icn)	I <sub>nc</sub> =I <sub>Δc</sub> =6000A
Rated Insulation Voltage [Ui]	415V
Rated Impulse Withstand Voltage [Uimp]	4000V
Mechanical Durability	10000 cycles
Electrical Durability	4000 cycles
Tightening Torque	M5 2.5N.m II
IP Degree of Protection	IP20 conforming to IEC 60529 IP40(modular enclosure) conforming to IEC 60529
Ambient Air Temperature for Operation	-5°C~40°C
EU RoHS Directive	Compliant EU RoHS Declaration
Pollution Degree	2 conforming to IEC/EN 60898-1
Upper Wiring	1-25mm <sup>2</sup>
Lower Wiring	

### Dimensions

