



# ET Series

## 40/50kW | Three Phase | 3/4 MPPTs Hybrid Inverter (HV)

GoodWe's ET Series inverters, available in 40kW and 50kW capacities, are designed for commercial and industrial PV installations. These adaptable inverters seamlessly integrate into both on-grid and off-grid applications, facilitating parallel connections in either scenario. When paired with the Static Transfer Switch (STS) Box from GoodWe, the inverter not only ensures dependable UPS-level switching to backup mode but also interacts with diesel generators to efficiently replenish batteries. Moreover, the ET Series is compatible with diverse battery capacities and brands, including the GoodWe Lynx C, offering a comprehensive energy storage solution.



### Flexible & Adaptable Applications

- Supports parallel connection in both on- and off-grid modes
- Up to 150% DC input oversizing
- 4 MPPTs, Max. efficiency up to 98.1%



### Superb Safety & Reliability

- Optional Type I+II SPD on DC side<sup>1</sup>
- IP66 protection for outdoor installation safety
- AFCI optional<sup>1</sup>



### Smart Control & Monitoring

- 110% unbalanced output
- UPS-level switching



### Friendly & Thoughtful Design

- Elegant and compact design
- Plug & Play installations



Technical Data	GW40K-ET-10	GW50K-ET-10
<b>Battery Input Data</b>		
Battery Type		Li-Ion
Nominal Battery Voltage (V)		500
Battery Voltage Range (V)		200 ~ 800
Start-up Voltage (V)		200
Number of Battery Input		1
Max. Continuous Charging Current (A)		100
Max. Continuous Discharging Current (A)		100
Max. Charging Power (W)	44000	55000
Max. Discharging Power (W)	44000	55000
<b>PV String Input Data</b>		
Max. Input Power (W) <sup>1</sup>	60000	75000
Max. Input Voltage (V) <sup>2</sup>		1000
MPPT Operating Voltage Range (V)		165 ~ 850
Start-up Voltage (V)		200
Nominal Input Voltage (V)		620
Max. Input Current per MPPT (A)	42 / 32 / 42	42 / 32 / 42 / 32
Max. Short Circuit Current per MPPT (A)	55 / 42 / 55	55 / 42 / 55 / 42
Number of MPP Trackers	3	4
Number of Strings per MPPT		2
<b>AC Output Data (On-grid)</b>		
Nominal Output Power (W)	40000	50000
Nominal Apparent Power Output to Utility Grid (VA)	40000	50000
Max. Apparent Power Output to Utility Grid (VA)	40000	50000
Max. Apparent Power from Utility Grid (VA)	40000	50000
Nominal Output Voltage (V)		380 / 400, 3L / N / PE
Output Voltage Range (V) <sup>3</sup>		176 ~ 276
Nominal AC Grid Frequency (Hz)		50 / 60
AC Grid Frequency Range (Hz)		45 ~ 65
Max. AC Current Output to Utility Grid (A)	60.6	75.8
Max. AC Current From Utility Grid (A)	60.6	75.8
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)	
Max. Total Harmonic Distortion	<3%	
<b>AC Output Data (Back-up)*requires additional STS box</b>		
Back-up Nominal Apparent Power (VA)	40000	50000
Max. Output Apparent Power (VA)	44000 (48000 @ 60sec, 60000 @ 10sec)	55000 (60000 @ 60sec, 75000 @ 10sec)
Max. Output Current (A)	66.7	83.3
Nominal Output Voltage (V)		380 / 400, 3L / N / PE
Nominal Output Frequency (Hz)		50 / 60
Output THDv (@Linear Load)	< 3%	
<b>Efficiency</b>		
Max. Efficiency	98.1%	
European Efficiency	97.5%	
Max. Battery to AC Efficiency	97.7%	
MPPT Efficiency	99.0%	
<b>Protection</b>		
Residual Current Monitoring	Integrated	
PV Reverse Polarity Protection	Integrated	
Battery Reverse Polarity Protection	Integrated	
Anti-islanding Protection	Integrated	
AC Overcurrent Protection	Integrated	
AC Short Circuit Protection	Integrated	
AC Overvoltage Protection	Integrated	
DC Switch	Integrated	
DC Surge Protection	Type II (Type I + II Optional)	
AC Surge Protection	Type II	
AFCI	Optional	
Remote Shutdown	Integrated	
<b>General Data</b>		
Operating Temperature Range (°C)	-35 ~ +60	
Relative Humidity	0 ~ 95%	
Max. Operating Altitude (m)	4000	
Cooling Method	Smart Fan Cooling	
User Interface	LED, WLAN + APP	
Communication with BMS	CAN	
Communication with Meter	RS485	
Communication with Portal	LAN / 4G (Optional)	
Weight (kg)	62	65
Dimension (W × H × D mm)	520 × 660 × 260	
Topology	Non-isolated	
Self-consumption at Night (W)	< 15	
Ingress Protection Rating	IP66	
Mounting Method	Wall Mounted	

\*1: In Australia, for most of the PV module, the max. Input power can achieve 2\*Pn. Such as the max. input power of GW50K-ET can achieve 100000W.

\*2: When the input voltage is greater than 980V, the inverter will enter standby mode, and when the voltage returns to below 970V the inverter will return to normal operation.

\*3: Output Voltage Range: phase voltage.

\*: Please visit GoodWe website for the latest certificates.